





Technical Specifications

Light Source	LED, Horticultural Grade, Anti-Sulfurization
Spectrum	Flower/Veg (PhD Designed)
PPF	1600 $\mu\text{mol/s}$
Input Power	715W @ 277VAC
Efficacy	2.2 $\mu\text{mol/J}$ @ 277VAC
Input Voltage	Autosensing 90-305VAC @ 50/60Hz
Dimensions	46.0"L x 44.5"W x 2.9"H (116.8cm x 113.0cm x 7.4cm)
Weight	36.4lbs (16.5kg)
Mounting Height	6" to 36" (15.2cm to 91.4cm) Above Canopy
Thermal Management	Passive with Graphite Thermal Interface
Heat Output	2439 BTU/hr @ 277VAC
Max. Ambient Temp	104°F (40°C)
Dimming	0-10VDC (<0.5V = off)
Light Distribution	120°
Lifetime	L90: >65,000 Hours
AC Power Cord	15ft (4.57m), 14/3 AWG
Power Factor	>90%
Certifications	ETL Damp; FCC / Canada Part 15a
Warranty	7 Year Standard Warranty



Maximum Current per Luminaire

AC Voltage	Current
120V	6.22A
208V	3.47A
240V	3.01A
277V	2.62A



Model	AC Plug Type	Mounting Hardware	Adaptive Controller
TR6	-515P NEMA 5-15P (120V) -615P NEMA 6-15P (220V/240V) -L715 NEMA L7-15P (277V) -HW01 Hard Wire (120-277V)	-H01 10ft Adjustable #2 Wire with Hooks -H02 6in Rack Hanging Hooks -H03 Gripple™ Adjustable Hangar System	-00 None (Warehouse) -LS01 LS-01 (Greenhouse)